

# NEW FROM SOLAX

## X1-BOOST G4



### X1-BOOST G4

2.5kW / 3.0kW / 3.3kW / 3.6kW  
4.2kW / 5.0kW / 6.0kW

## Features

### Superior Performance

- DC Input: 200% oversizing, 16A current, 50V startup voltage
- In-built global MPP scan for higher yield efficiency

### User Friendly Monitoring

- 10s level interval of data update(Optional, new WiFi dongle required)
- Quick and easy configuration (WiFi&APP)

### Assured Safety & Reliability

- AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported
- Optional external RSD (Rapid Shutdown) and integrated DC AFCI protection (Optional)
- In-built export control function

### Superb Adaptability

- Home EV Charger and Heat Pump Solution adaptable
- Mass management and broad extension via Datahub
- Master/Slave parallel solution via Modbus supported

### Contact Us for More Information

[www.solaxpower.com](http://www.solaxpower.com)

AU: +61 1300 476529

DE: +49 6142 4091664

Global: +86 571-56260008

UK: +44 2476 586998

NL: +31 (0) 852 737932

[info@solaxpower.com](mailto:info@solaxpower.com)  
[service@solaxpower.com](mailto:service@solaxpower.com)



## DC INPUT

Max. PV array input power [Wp]	5000	6000	6600	7200	8000	10000	12000
Max. PV input voltage [V]	600	600	600	600	600	600	600
Startup voltage [V]	50	50	50	50	50	50	50
Nominal input voltage [V]	360	360	360	360	360	360	360
MPP tracker voltage range [V]	40~560	40~560	40~560	40~560	40~560	40~560	40~560
No. of MPP trackers / String per MPP tracker	2 / 1						
Max. PV input current[A]	16 / 16						
Isc PV Array Short Circuit current [A]	22 / 22						

## AC OUTPUT

Rated AC output power [W]	2500	3000	3300	3680	4200	5000 <sup>①</sup>	6000
Rated AC output current [A]	10.9	13	14.3	16	18.3	21.7	26.1
Max. AC output apparent power [VA]	2800	3300	3630	4048 <sup>④</sup>	4620	5000 <sup>②</sup>	6000
Max. AC output current [A]	13.3	14.3	15.7	17.6 <sup>⑤</sup>	20.1	21.7 <sup>③</sup>	27.3
Nominal AC voltage / AC voltage range [V] **	220/230/240;90~290						
Nominal AC frequency / AC frequency range [Hz] **	50/60;±5						
Power Factor range	0.8leading~0.8lagging						
THDi (rated power) [%]	<3						

## SYSTEM DATA

Max. Efficiency [%]	98						
Euro. Efficiency [%]	97						
Standby consumption [W] @Night	<3						
Ingress protection	IP66						
Operating ambient temperature range [°C]	-25~60						
Max. operation altitude [m]	4000						
Relative humidity [%]	0~100						
Typical noise emission [dB]	25 <sup>⑥</sup>						
Storage temperature [°C]	-30~70						
Dimensions (W x H x D) [mm]	404x274x146						
Weight [kg]	11						
Cooling concept	Nature cooling						
Communication interfaces	USB/RS485/DRM, Optional: Meter/CT *						
Optional monitoring dongle	Pocket WiFi/LAN/4G						
Display	2 x LED + LCD (16 x 2) / APP						

## PROTECTION

Over / under voltage protection	Yes						
DC isolation protection	Yes						
Monitoring ground fault protection	Yes						
Grid monitoring	Yes						
DC injection monitoring	Yes						
Back feed current monitoring	Yes						
Residual current detection	Yes						
Anti-islanding protection	Yes						
Over temperature protection	Yes						
SPD (DC/AC)	Type II / Type II (Optional)						
Arc-fault circuit interrupter (AFCI)	Optional						
AC auxiliary power supply (APS)	Optional						
DC Switch	Optional						

## STANDARD

Safety	IEC / EN 62109-1 / -2						
EMC	EN61000-6-1 / 2 / 3 / 4, EN61000-3-2 / 3 / 11 / 12						
Certification	IEC61727, EN50549, G98/G99, AS 4777.2, VDE4105, CEI 0-21, VFR, PPDS, TOR						

① 5000 (4600 for VDE4105) ② 5000 (4600 for VDE4105) ③ 21.7 (20 for VDE4105) ④ 4048 (3680 For G98/G99, TOR and PPDS) ⑤ 17.6 (16 For G98/G99, TOR and PPDS)

⑥ For models with internal fan(Optional), typical noise emission is 30 dB

\* Not included in the package. Please purchase additionally. \*\* The AC voltage and the frequency range may vary from different country codes.

\* V1.1. Information may be subject to modify without notice.650.00029.00